



# MOTALA 2000 CABIN

LARGEST INSIDE SMALLEST OUTSIDE

**MOTALA**  
H I S S A R




## BIG LIFT COMFORT IN A SMALL PACKAGE



## LIFETIME WARRANTY

ON CHAIN DRIVE



## 2000 CABIN LIFTS

- ✓ DRIVE SYSTEM GUIDED CHAIN
- ✓ SILENT AND SAFE
- ✓ EXTREMELY SPACE EFFICIENT
- ✓ LOW MAINTENANCE REQUIREMENTS

MOTALA 2000 CABIN ENHANCES THE  
VALUE OF YOUR PROPERTY AND HELPS  
MAKE IT ACCESSIBLE FOR ALL.

[WWW.MOTALAHISSAR.SE](http://WWW.MOTALAHISSAR.SE)



# Motor and gearbox

- Five years warranty
- Power: 1.1 kW
- Nominal speed: 1400 rpm
- Gearbox: 32:1
- Soft stop and start

# Environmentally friendly

- More energy efficient than other platform lifts
- Life time oil in gearbox
- 95% recyclable

# Standard features

- LED lights in cabin ceiling
- Stainless steel handrail
- Load weighing device
- Electrical emergency lowering device
- Control cabinet integrated on top door frame
- Self supporting shaft

# Options

## Sizes

- (1250x1560) , (1250x1760)

## Doors

- Doors can be fitted on two sides of the shaft A-C
- Automatic operation
- Right or left-hand opening
- Certified fire doors available

## Shaft walls with steel panels

- Aluzinc steel
- Powder coated white (RAL9010) as standard
- Glazing on 4 sides available

## Cabin

- Glazing on two sides
- If door on C- side glazing only possible on one side (drive side)

# Lift for indoor installation

Travel:	Max 15m.
Speed:	0.15 m/s.
Stops:	2-6
Doors:	Swing door 900 x 2000 mm.
Rated load:	Max 440 kg.
Headroom required:	2200 mm above top landing
Supply voltage:	Single phase 230-240V 10 A.
Drive system:	Guided chain system with gear lubricated for life. 1.1 kw asynchronous electric motor. Safety gear and overspeed governor.
Shaft:	Self-supporting structure.No need for conventional shaft or supporting wall. Shaft height on top landing is 2200 mm.
Pit:	70 mm depth; or ramp.
Cabin:	Fully enclosed with automatic sliding door
Control system:	Microprocessor controlled PLC.
Emergency lowering:	Automatic emergency lowering to nearest landing below; or manual lowering.
Alarm:	Battery-powered, automatic recharging alarm system. Optional, two-way voice communication, auto-dialer.
Certification	Certified European Union Machinery Directive 2006/42/EC and European Harmonised Standard EN81-41.

# CONTACT

+46 141 23 70 50

WWW.MOTALAHISSAR.SE