

MOTALA B6 OPTIONS





THE MOST SPACE EFFICIENT LIFT - TECHNICAL INFORMATION AND ADDITIONAL OPTIONS

Available sizes in mm

Shaft sizes

Shaft width → Shaft depth ~	750	800	850	900	950	1000	1050	1100	1150	1200	1250	1300
1000	•	•	•	•	•	•	•	•	•	•	•	•
1050	•	•	•	•	•	•	•	•	•	•	•	•
1100	•	•	•	•	•	•	•	•	•	•	•	•
1150	•	•	•	•	•	•	•	•	•	•	•	•
1200	•	•	•	•	•	•	•	•	•	•	•	•
1250	•	•	•	•	•	•	•	•	•	•	•	•
1300	•	•	•	•	•	•	•	•	•	•	•	•
1350	•	•	•	•	•	•	•	•	•	•	•	•
1400	•	•	•	•	•	•	•	•	•	•	•	•
1450	•	•	•	•	•	•	•	•	•	•	•	•
1500	•	•	•	•	•	•	•	•	•	•	•	•
1550	•	•	•	•	•	•	•	•	•	•	•	•
1600	•	•	•	•	•	•	•	•	•	•	•	•
1650	•	•	•	•	•	•	•	•	•	•	•	•
1700	•	•	•	•	•	•	•	•	•	•	•	•
1750	•	•	•	•	•	•	•	•	•	•	•	•
1800	•	•	•	•	•	•	•	•	•	•	•	•
1850	•	•	•	•	•	•	•	•	•	•	•	•
1900	•	•	•	•	•	•	•	•	•	•	•	•
1950	•	•	•	•	•	•	•	•	•	•	•	•
2000	•	•	•	•	•	•	•	•	•	•	•	•
2050	•	•	•	•	•	•	•	•	•	•	•	•
2100	•	•	•	•	•	•	•	•	•	•	•	•
2160	•	•	•	•	•	•	•	•	•	•	•	•

See corresponding car sizes in table on the next page

- Standard size
- Available size as option
- Not available

Available sizes in mm

Car sizes

Car width → Car depth ~	550	600	650	700	750	800	850	900	950	1000	1050	1100
850	•	•	•	•	•	•	•	•	•	•	•	•
900	•	•	•	•	•	•	•	•	•	•	•	•
950	•	•	•	•	•	•	•	•	•	•	•	•
1000	•	•	•	•	•	•	•	•	•	•	•	•
1050	•	•	•	•	•	•	•	•	•	•	•	•
1100	•	•	•	•	•	•	•	•	•	•	•	•
1150	•	•	•	•	•	•	•	•	•	•	•	•
1200	•	•	•	•	•	•	•	•	•	•	•	•
1250	•	•	•	•	•	•	•	•	•	•	•	•
1300	•	•	•	•	•	•	•	•	•	•	•	•
1350	•	•	•	•	•	•	•	•	•	•	•	•
1400	•	•	•	•	•	•	•	•	•	•	•	•
1450	•	•	•	•	•	•	•	•	•	•	•	•
1500	•	•	•	•	•	•	•	•	•	•	•	•
1550	•	•	•	•	•	•	•	•	•	•	•	•
1600	•	•	•	•	•	•	•	•	•	•	•	•
1650	•	•	•	•	•	•	•	•	•	•	•	•
1700	•	•	•	•	•	•	•	•	•	•	•	•
1750	•	•	•	•	•	•	•	•	•	•	•	•
1800	•	•	•	•	•	•	•	•	•	•	•	•
1850	•	•	•	•	•	•	•	•	•	•	•	•
1900	•	•	•	•	•	•	•	•	•	•	•	•
1950	•	•	•	•	•	•	•	•	•	•	•	•
2010	•	•	•	•	•	•	•	•	•	•	•	•

The car size corresponds to the shaft size. The car width equals shaft width minus 200 mm and the car depth equals shaft depth minus 150 mm.

- Standard size
- Available size as option
- Not available

Glass options



Ocean 1



Ocean 2



Smoke 1



Smoke 2



Bronze 1



Bronze 2



Frosted 1



Frosted 2

wall cladding options



Floor options



Smoke Gray





Coral Red



Dallas Black



Denver Gray



Flakey Gray

Colours



RAL colour scale for lift shaft, doors and platforms

Doors



Faac intelligent (automatic)

MH-Swing (automatic)

Folding chair



Car glass



COP- additional option



According to EN81-70 Appendix B

If COP according to Appendix B is chosen it will be an addition to the standard COP.

Landing Call Station (LCS) – with floor display



AIDA

Hall lantern



LCS-AIDA cannot be combined with hall lantern (floor display) at the same floor. Hall lantern will be placed on door frame.

Key operation



Possibility to lock one or more floors at COP. Possibility to lock landing call stations (LCS) to prevent unauthorized use of the lift.

Emergency phone



Two way emergency phone



MƏTALA

LARGEST INSIDE SMALLEST OUTSIDE

CONTACT

+46 141 23 70 50 www.motalahissar.se This document provides an overview of the technical specifications and available options for Motala B6. The brochure contains general information, and we reserve the right to change design and specifications at any time. No statements in this document should be construed as warranties or conditions, expressed or implied, of any product, its suitability for any purpose or quality, or any modification or presentation of the terms of any purchase agreement. Minor deviations between printed and actual colors may occur. The brand Motala and Motala B6 are owned by Motala Hissar AB.